



APart PA-CONFCL CONFERENCE MICROPHONE TERMINAL

APart



The Apart PA-CONFCL is a high quality build-in chairman microphone terminal that can be used in combination with the Apart PA-CONF microphone system. The chairman build-in unit has an unobstructive design. The microphone base is equipped with a "SPEECH" and "PRIORITY" button. Pushing the "SPEECH" button activates the microphone and the red led on the base will lighten together with the red led ring on below the microphone wind shield..

Pressing the "PRIORITY" button, will mute all delegate microphones that are behind the PA-CONFCL in the daisy chain. A few Seconds after the "PRIORITY" button has been released, the delegate units (PA-CONFCL) can be activated again by pushing their "SPEECH" button. The build in limiter improves the intelligibility and prevents big level differences between silent and "shouting" speeches.

The microphone base is equipped with a 3 pin XLR input in which the included microphone can be plugged in. Every microphone base has a stereo jack input and output. The delegate units can be connected via daisy chaining. This way, linking the cables to the delegate units is very easy (2 m cables included).

The microphone has a high quality Japanese uni-directional condenser microphone capsule. Due to the quality of the microphone, feedback problems in most cases won't occur. It has a sturdy but very elegant and slim stem with a flexible part at the top & bottom. A red LED ring on top of the microphones stem indicates if the microphone is activated.

All these features, together with the unique PA-CONF microphone system, result in a very competitive and versatile system that can be used for meeting rooms (replaces the standard 10 channel microphone mixer), small conference systems and others. Thanks to the build-in microphone base, the unit takes very little place. Above all, installing this system is very easy.

TECHNICAL SPECIFICATIONS

Type	Table type Condensator microphone
Polar pattern	Uni-directional cardioid
Input Base	6.3 mm jack (1: Signal / 2: Conference power / 3: Ground)
Microphone	XLR 3
Output	6.3 mm jack (1: Signal / 2: Conference power / 3: Ground)
Frequency range	150 Hz - 16 kHz (-3dB)
Sensitivity	-68 dB
Limiter	Build-in
Light ring	Yes
Cable	6.3mm jack cable, 2 m
Dimensions Base (H x W x D)	62 x 142 x 125 mm
Microphone (L)	470 mm
Weight (base + mic)	0.75 Kg